


FEWER LAYERS MORE PROTECTION

ATS® PE UD AP220

Outstanding performance, PE UD 4-ply for ballistic vests and ballistric plates.

ATS® PE UD AP220 deliver outstanding performance for ballistic vests and ballistic plates and can be combined with other materials with a reduced number of layers, achieving a superior balance between lightweight, high-performance and soft ballistic solutions at a lower cost.

Proper handling
Avoid tearing and crushing the product.

Proper storage
Store in dry temperate area avoiding storage conditions exceeding 60°C (140°F) and avoiding direct exposure to sun or UV light. Cover the product with black impermeable plastic.

Stack layers in the same direction and orientation to achieve optimal performance.
It is the responsibility of the armor manufacturer to design suitable products and obtain the relevant certifications before releasing end products using ATS® PE UD AP220.

Do not use bleach or products containing bleach to clean ATS® PE UD AP220.

ATS® PE UD AP220 have been tested according to NIJ 0101.04 / NIJ 0101.04 protocol.

TECHNICAL DATA

Property	Nominal aim
Width	160 cm
Length	100- 150 mt
A220 Areal density*	220 g/m2

*Conditioned Weight, 20°C / 65 RH (ASTM D1776)

www.ats.com.mk
www.atsballistics.mk
info@ats.com.mk